Permit #
Parcel #
nstruct, alter or resurface with:
vel/other
☐ REPLACEMENT
Phone
ole from the street/highway at ST BE INSPECTED 1 DAY ment.
AREA
AREA
AREA Lot line to Driveway
T.
T.
T.

VILLAGE OF PLOVER

DRIVEWAY							
(Permit is for	that part of the drivev			nstruct, alter or resurface	with:		
			Granite/gray		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Fee \$20	TEDAID	_ ⊔	Blacktop				
D.F.	ATE PAID		Concrete				
Address of Driveway location	1		□ NEW	☐ REPLACEMENT			
wner Telephone		Cell	Phone				
Mailing Address:							
IMPORTANT: Please plac the location of the driveway PRIOR TO COMPLETION	approach. ALL	DRIVEWAY LA	YOUTS MU	ST BE INSPECTED 1			
Driveway Information:	Expected date of	work					
	Contractor's nar	ne					
	Phone No.		Cell Phone				
Contractor's address							
	Cost of Project						
co	MPLETE INFO	RMATION IN	SKETCH A	AREA			
This line represents the lot line along road							
Lot line to Driveway ◆		25' MAX. Driveway Width at Lot line		Lot line to Driveway ◆			
Ditch and Should	ler Area						
Corner lot	No/		,				
				ions and conditions cont			
n this permit and have read an neluding the plot plan and pro			ons of Village	of Plover Code Chapter	260,		
FORM 20		IVEWAY APPRO)ACH	PAGE 1	OF 2		

REVISED 6/1/2016

RIGHT-OF-WAY

No private structures or objects may be placed in the road right-of-way. The Village of Plover will not be responsible for such illegally placed structures or objects and has the right pursuant to Sec. of Wis. Stat. to order the removal of any object or structure which lies in the right-of-way. Personal use of road right-of-way is limited to planting or maintaining. Any portion of driveway must be limited to perceived lot line extensions to roadway.

ROADWAY DITCHES

Roadway ditches shall be constructed consistent with the specifications on the attached diagram.

No property owner shall modify an existing roadway ditch in such a manner as to cause the depth to vary from the greater of the original elevation or a depth nine inches below the edge of the paved surface of the road. Up to four inches of topsoil may be placed on the right-of-way from the lot line to the outside edge of the roadway shoulder but must maintain a finished depth of nine (9) inches. In any event, no property owner may modify an existing roadway ditch, nor install a driveway without culvert pipes, so as to impede the natural drainage of water.

The Village of Plover Public Works Manager shall have authority to order, in the interests of the public safety, health, and welfare, that a deeper roadway ditch is required for drainage or road preservation.

SHOULDERS

All newly constructed roadways within the Village of Plover shall have a 3' minimum shoulders which consists of a gravel or aggregate road base.

If existing blacktopped roads are overlaid, the shoulder shall be of reasonable width consisting of a gravel or aggregate road base.

DRIVEWAYS

Driveway approaches may be constructed of the following material: bituminous, gravel, granite, sand, sod, concrete, and such materials as the Village of Village Public Works Manager may approve from time to time in order to protect road grading equipment.

When grading or reconstructing a roadway, the Village of Plover will replace existing driveway(s) for each separate freehold. The portion of the driveway approach to be replaced will be from the portion of the edge of the roadway to the edge of the abutting right-of-way. A driveway shall be replaced with a surface similar to its original surface except for concrete. For a concrete approach the property owner will have the option of accepting a bituminous approach or accepting a payment from the Village of Plover equal to the cost of a bituminous replacement.

Office Use Only:		
CULVERT IS REQUIRED NOT REQUIRED	DiameterLengthDepth Culvert must be installed by:	
ENDWALL REQUIRED NOT REQUIRED		
by:		
Permit mailed to resident:	Copy to Crew	